



MANUFACTURERS OF SUPERIOR FLUORESCENT LUMINAIRES

PROJECT LUMINAIRE TYPE

## FEATURES

- Vandal-proof alloy construction.
- High-impact UV stable polycarbonate lens.
- Stainless steel threads, fasteners and glands.
- Powder-coated finish over chromated alloy.
- Allen key stainless access screws.
- Energy efficient electronic control gear.
- Available in PL and LED lamp options.
- Complete with plaster recessing bracket.
- Internal anti-glare louvre.
- Designed and made in Australia.



## CORRIDOR LIGHT



### Specifications

Length	244mm 7w & 9w	300mm 11w
Width (W)	80mm	
Recess Depth (D)	70mm ( Suit standard stud wall )	

Specifications subject to change without notice

## ORDERING INFORMATION

Examples: **ITCL 118 / EL**  
**ITCL 2B LED / EL**

### ITCL

Series	No. of Lamps	Lamp Type	Diffuser as STD	Control Gear Options
ITCL	1	<b>07</b> 7W PL	Clear Reed with louvre	<b>EL</b> Electronic Ballast
	1	<b>09</b> 9W PL	Clear Reed with louvre	
	1	<b>11</b> 11WPL	Clear Reed with louvre	
	<b>2W</b> - White	<b>LED</b> Diffused	Opal Reed	
	<b>2B</b> - Blue	<b>LED</b> Diffused	Opal Reed	
	<b>1B</b> - Blue	<b>LED</b> Effect	Clear Reed	
	<b>1Y</b> - Yellow	<b>LED</b> Effect	Clear Reed	
	<b>1R</b> - Red	<b>LED</b> Effect	Clear Reed	
	<b>1G</b> - Green	<b>LED</b> Effect	Clear Reed	